

ViewSonic®

VE150m/VE150mb LCD Display



- Full 15.0" viewable screen
- 1024 x 768 true resolution
- OnView® controls including ViewMatch® feature
All screen adjustments are made via an on-screen menu using simple controls.
- AutoTune® function
Automatically monitors video input and optimizes display settings without requiring user adjustments.
- Slim 1.9" profile (panel only)
- Bezel-integrated speakers
- Anti-reflective coating
Minimizes glare and reflections, reducing eyestrain and allowing for optimal viewing comfort.

15" TFT Multimedia LCD Color Display.

The VE150m and VE150mb multimedia LCD displays produce sharp, crisp text and images with a high contrast ratio of 300:1 (typ) and no screen flicker. Offering our fully automatic, AutoTune feature, the VE150m and VE150mb self correct for video card anomalies like drift and non-VESA® video timing, delivering the best possible image in all environments. At only 1.9-inches thin, this display is perfect for government, real estate or medical offices and financial industries where space is at a premium. And the built-in speakers sound great, even when the display is wall mounted. The ViewSonic VE150m and VE150mb LCD displays are a solid choice for users who want a lightweight, reliable, value-priced LCD display.



ViewSonic®
See the difference.®

ViewSonic®

VE150m/VE150mb LCD Display



• VE150mb black case version†

• ViewSonic Wizard

The ViewSonic Wizard software provides user-friendly installation. The enclosed CD-ROM automates the set-up process to deliver optimized screen performance.

• TCO Energy certified

This monitor complies with the world's strictest standards of low radiation, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.



• PC & Mac® compatible*

• Kensington® security port

Kensington security port protects your assets.

• Three-year limited warranty

• VESA-compliant 75mm wall mount (optional)

The ViewSonic Universal Wall Mount provides full ViewPanel® tilt, side-to-side tilt and portrait/landscape rotation, adding ergonomic adjustability and space savings.



15.0" TFT MULTIMEDIA DISPLAY

VIEWPANEL	Type	TFT active matrix (16.7 million colors)
	Display Area	15.0" viewable
	Contrast Ratio	300:1 (typ)
	Viewing Angle	120° horizontal, 95° vertical (typ)
	Light Source	Long life, 50,000 hrs. (min)
	Response Time	30ms
	Brightness	300 cd/m ² (typ)
	Glass Surface	Anti-glare coat
ANALOG INPUT	Video	RGB Analog (75 ohms, 0.7/1.0 Vp-p)
	Frequency	F _H :30-60kHz, F _V :50-75Hz
	Sync	H/V Separated (TTL)
COMPATIBILITY	PC	PC compatibles from VGA up to 1024x768 non interlaced
	Mac®*	Power Mac™ (up to 1024x768)
CONNECTORS	Analog RGB	15-pin mini D-sub (attached)
	Power	DC IN into head
	Audio Input	Stereo mini jack
AUDIO	Speaker	Two 1.5W speakers
	Amplifier	1.5w at 1kHz for THD 1%
POWER	Voltage	AC 100–240V (Universal) via external DC converter brick
	Consumption	30W (typ)
CONTROLS	Physical	1, down, up, 2, power, Volume up, Volume down, Mute
	OSD/Analog Input	Contrast, brightness, auto sync, H/V position, ViewMatch® color, H/size, H/V position, fine tune, Auto image adjust, sharpness, OSD position smoothing, ViewMeter®, input select, language, auto contrast, mute, volume, recall, OSD time out resolution notifier
OPERATING CONDITION	Temperature	32°F–104°F (0°C to 40°C)
		10%–90% (no condensation)
DISPLAY AREA		304mm (H) x 228mm (V)
DIMENSIONS	Physical	374mm (W) x 351mm (H) x 135mm (D)
		14.9" (W) x 13.8" (H) x 5.4" (D)
WEIGHT	Net	4.4 kg (9.7 lbs.)
OTHER		DDC1 & DDC2B
REGULATIONS		UL, CSA, FCC-B, CB, CE, IC-B, EPA, NOM, TUV/GS, VCCI, BMSI, PSB (S-Mark), C-Tick, GOST-R (PCT BZ02), PCBC (B-Mark), EMI/B, MPRII, NEMKO, SEMKO, DEMKO, FIMKO, ISO13046-2
POWER MANAGEMENT		Meets VESA® DPMS™, TCO and Energy standards
WARRANTY		Three-year limited warranty on parts, labor and backlight.



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



ViewSonic®
See the difference.®

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Phone (800) 888-8583 or (909) 444-8888 • In Canada (866) 262-1967 • Fax (909) 839-7922 • SalesInfo@ViewSonic.com • ViewSonic.com

*May require the use of the VS cable for older systems. †VE150mb is TCO'95 compliant. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. Microsoft, Window NT, Windows 2000 and the Windows logos are the registered trademarks of Microsoft Corporation in the United States and other countries. Copyright © 2003, ViewSonic Corporation. All rights reserved. VSVE150m_05/01_20k [10203-02B_03/03] VS-2231