

## Fujitsu recommends Windows Vista® Business.

## LifeBook S7210

- 14.1-inch wide Intel® Centrino® Duo LifeBook at approximately 2.2kg\*
- Genuine Windows Vista® Business
- Instant converged communications using built-in 1.3 Mega Pixel camera and dual built-in stereo microphones
- Superior security features for enhanced data and hardware protection
- Hot-swappable modular bay device options for ultimate flexibility
- Health and environment friendliness with RoHS compliance<sup>10</sup>



\*with weight saver option only

## Specifications

Platform	Intel® Centrino® Duo processor technology - Intel® Core™2 Duo Processor T7500 <sup>5</sup> (2.2GHz, 4MB L2 cache, 800MHz) - Intel® GM965 Express Chipset - Intel® PRO/Wireless 4965AGN/3945BG wireless connection
Operating System	Genuine Windows Vista® Business (or Genuine Windows Vista® Home Premium) (or Genuine Windows Vista® Home Basic)
Display	14.1-inch WXGA TFT, 1280 x 800 pixels
Modular Bay Device	Dual Layer DVD Super Multi Writer <sup>9</sup> / DVD/CD-RW Combo Drive
Memory	1GB DDR2 667MHz Max. Memory Supported <sup>14</sup> - 4GB DDR2 667MHz, Dual-Channel
Intel® Turbo Memory <sup>3</sup>	1GB
Hard Disk	160GB
Battery	Up to 3.5hrs <sup>1</sup> (6-cell Li-Ion 5800mAh)
Weight	Approx. 2.2kg (w/ weight saver option)
<b>Detailed Specifications</b>	
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/50 <sup>13</sup> , protected by Fujitsu 3D Shock Sensor <sup>15</sup>
Graphics	Integrated Intel® Graphics Media Accelerator X3100 with Intel® Clear Video Technology <sup>11</sup> and DVMT <sup>12</sup> 4.0 delivers low-power, high-performance 2D/3D graphics with Shader Model 3.0, video and display capabilities at a max. shared memory of 384MB
High Definition (HD) Audio	RealTek ALC262 HD audio codec with dual built-in stereo speakers HD Audio-in: External Mic-in, Dual Built-in Stereo Microphones HD Audio-out: Headphone-out
Communication	1.3 Mega Pixel CMOS camera, Bluetooth® v2.0+EDR, 56K V.92 <sup>2</sup> Global Modem MDC1.5, 1000/100/10Mbps <sup>4</sup> Gigabit Ethernet PCI Express x 1 and Intel® PRO/Wireless 4965AGN/3945BG wireless connection with three antenna. Separate ON/OFF switch for wireless network connection.
User Interface	Spill-resistant Keyboard <sup>12</sup> : 84-key, 19mm key pitch, 2.7mm key stroke, Quickpoint option Intelligent Touch Pad with configurable vertical and horizontal scroll functions Fingerprint Sensor with vertical scroll functions
Card Slots	ExpressCard™ /34 /54, Smartcard <sup>7</sup> , Secured Digital/ SDHC/ Memory Stick®/ Memory Stick® PRO
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), S-Video out, HDA-in, HDA-out, Power Adapter DC-in, Port Replicator Interface
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email, and two other softwares)
Security <sup>8</sup>	BIOS Lock, 2-password Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smartcard <sup>7</sup> slot, Fingerprint Sensor, Trusted Platform Module option
Dimensions	334mm (W) x 242mm (D) x 31/35mm (H)
<b>Bundled Accessories</b>	
AC Adapter	Input AC 100-240V, Output DC 19V 80W
Dual Layer DVD Super Multi Writer	Softex Omnipass, CyberLink PowerDVD™, CyberLink PowerProducer™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi <sup>16</sup> , Fujitsu 3D Shock Sensor Utility, Fujitsu Power Saving Utility, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Sun Microsystems Java Runtime, Camera Capture Application, Microsoft Office Professional 2007 60-day Convertible Trial <sup>18</sup>
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image
<b>Optional Accessories</b>	
Port Replicator	Connector Interface: USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in
Modular Bay Options	Replaceable with - Bay Battery, 6-cell Li-Ion 3800mAh, up to 6hrs <sup>1</sup> battery life (Standard + Bay Batteries) - Dual Layer DVD Super Multi Writer <sup>9</sup> - 2nd SATA HDD Fitting Kit <sup>17</sup> - DVD/CD-RW Combo Drive - Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	Optical USB Black Mouse (Retractable)

The above information shows the general technical specifications of the product and does not represent actual configuration that would be sold in your region. For specific configurations and their availability, please check with your local distributors.

- Results obtained from BAPCO® MobileMark® 2007 (Productivity Workload) performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running applications, connected peripherals, power management settings, battery conditioning, and other customer preferences in the real life situation. Built-in bay device or hard drive usage may also have a significant impact on battery life. Note: Battery life is based on Intel® Core™2 Duo Processor T7500.
- Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.
- Intel® Turbo Memory is a multi-component platform technology that uses non-volatile memory (Flash memory) to increase system responsiveness, make multi-tasking faster, and extend battery life.
- This term does not represent actual data rate of 1000/100/10Mbps and simply indicates compliance with IEEE 802.3, IEEE 802.3u and IEEE 802.3ab standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices.
- Please check actual bundling with country local distributor. T7500 (2.2GHz, 4MB L2 cache, 800MHz FSB).
- Dynamic Video Memory Technology (DVMT) dynamically responds to application requirement and efficiently allocates the proper amount of memory (max. 384MB) for optimal graphics and system performance. The memory size available to the Operating System will be less than the size of installed memory module.
- Fujitsu does not provide the application for Smartcard solution.
- BIOS Lock needs a supervisor/user password to access BIOS setup. BIOS settings can be configured to prompt for password at every first bootup or all bootup sequences. Access to BIOS setup is needed to configure Hard Disk Lock. Hard Disk Lock requires an access key to retrieve data on the hard disk. This is a Data Confidentiality security feature. LifeBook Lock requires a supervisor/user password to bootup the LifeBook when it powers up or resumes last session from suspend/hibernate mode. This is an anti-theft feature with more than 800,000 password combinations using the buttons on the Quick Launch Panel. Anti-theft Lock Slot allows the use of a lock to physically secure the LifeBook. Smartcard slot usage is dependent on customer's solution. Fingerprint sensor uses AuthenTec TruePrint™ Technology and Softex OmniPass to remember customer list of user IDs and passwords. Full security unlock sequence - LifeBook Lock, Bootup Lock (BIOS Lock), Hard Disk Lock, Fingerprint Windows Login.  
NOTE: Loss of password requires the LifeBook to be returned to Japan factory for system refresh. Cost of shipment and lost data will be borne by the customer. Backup your user's profile before changing HDD. Without the user's profile associated with a document at the point of encryption, Softex OmniPass cannot decrypt the encrypted document. 2 passwords refer to Master Password and User Password of the HDD Lock. The Master Password can be used to clear the User Password at the BIOS settings under Hard Disk Security. If HDD Lock prompt is enabled, only the User Password can be used to boot up the unit. Loss of these 2 passwords means the HDD content cannot be retrieved. It is the customer's responsibility to ensure the safe keeping of these 2 passwords for retrieval of data from the locked HDD.
- Supports DVD multi formats such as DVD-RAM, DL DVD+R, DVD+RW, DVD+R, CD-RW, DVD-ROM, CD-R and CD-ROM.
- RoHS (Restriction on Hazardous Substances) compliance means the system and its internal components comply with the EU RoHS directive (2002/95/EC) on the restricted use of six hazardous substances in the manufacture of the system and its internal components
- Intel® Clear Video Technology is a combination of video processing hardware and software technologies that delivers enhanced high-definition video playback, sharper images, precise color control and advanced support for a wide range of digital displays interfaces, including High-Definition Multimedia Interface (HDMI).
- Spill-resistant keyboard does not imply the system is water-proof. If liquid is spilled onto the keyboard, power off the system immediately and turn the notebook upside down to drain off the liquid.
- This refers to Windows Vista® hard disk drives C:\ and D:\. 50/50 refer to approximate 50% allocation of user accessible hard disk storage to C:\ and D:\ drives. For Windows Vista® hard disk drives, 1GB will be reserved for internal recovery usage which is not shown.
- 4GB DDR2 667MHz maximum memory is supported when Fujitsu recommended 2GB DDR2 667MHz memory module is made available.
- Fujitsu 3D Shock Sensor of a powered-up unit retracts hard disk read-write head to a secured zone upon detection of excessive vibrations or shocks. This greatly reduces the possibility of damage to the hard disk and its content - example in the event of a sudden drop or impact. The sensor monitors movement from three axes and its sensitivity can be adjusted by user to accommodate different working environments using the Fujitsu 3D Shock Sensor Utility.
- UpdateNavi is a Fujitsu Proprietary application that updates LifeBook drivers by connecting automatically to Fujitsu's server. This will help update your LifeBook with the latest software drivers and utilities to ensure compatibility between hardware and software, maintaining smooth operation anytime, anywhere.
- Only the HDD Housing Kit and screws are provided. HDD is to be purchased separately.
- Microsoft Office Professional 2007 60-day Convertible Trial needs online activation to begin. 60-day starts from day of activation.

"PCI Express" and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG.

Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

It is natural for all thin-film transistor (TFT) liquid crystal displays (LCD) to show a small number of missing or discoloured dots. These are commonly known as non-conforming pixels. This is a technology limitation of TFT LCD and does not represent a defect. Fujitsu warranty does not cover limitations in technology such as non-conforming pixels.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5° to 35°C / 41 to 95°F (operating), -15° to 60°C / 5 to 140°F (non-operating). Relative humidity: 20% to 85% RH (operating), 8% to 85% RH (non-operating). Please note that GB = billion bytes, 1GB is equivalent to 1,073,741,824 bytes.

## HONG KONG (Head Office):

## Fujitsu PC

## Asia Pacific Ltd

Tel : (852) 3101 8133

Fax : (852) 3101 0633

hk.fujitsu.com/pc

## AUSTRALIA &amp; NEW ZEALAND:

## Fujitsu PC Australia

Toll Free: (AU) 1800 288 283

(NZ) 0800 288 283

Fax : (61-2) 9889 3360

## CHINA:

## Fujitsu PC China Division

Tel : (86-21) 3310 9888

Fax : (86-21) 3310 0606

cn.fujitsu.com/pc

## INDIA:

## Fujitsu India Limited

Tel : (91-11) 2370 6070

Fax : (91-11) 2370 6079

## INDONESIA:

## Fujitsu Indonesia

Tel : (62-21) 570 9330

Fax : (62-21) 573 5150

## MALAYSIA:

## Fujitsu PC Asia Pacific Pte Ltd

Tel : (60-3) 7728 4868

Fax : (60-3) 7728 4830

my.fujitsu.com/pc

## PHILIPPINES:

## Fujitsu Philippines Inc.

Tel : (63-2) 812 4001

Fax : (63-2) 817 7576

ph.fujitsu.com/pc

## SINGAPORE:

## Fujitsu PC Asia Pacific Pte Ltd

Tel : (65) 6776 0688

Fax : (65) 6776 0788

sg.fujitsu.com/pc

## TAIWAN:

## Fujitsu Taiwan Ltd

Tel : (886-2) 2311 2255

Fax : (886-2) 2311 2277

## THAILAND:

## Fujitsu Systems Business (Thailand) Ltd PC Division

Tel : (66-2) 263 7888

Fax : (66-2) 263 7880

## VIETNAM:

## Fujitsu Vietnam Ltd

Tel : (84-4) 831 3895

Fax : (84-4) 831 3898

## Note: For countries not listed above, please contact our Hong Kong office.



All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in this documentation is correct and fairly stated, but does not accept liability for any errors or omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.

Dealer: