

Fujitsu recommends Windows Vista® Business.

LifeBook S7220

- 14.1-inch wide Intel® Centrino® Duo LifeBook at approximately 2.2kg*
- Genuine Windows Vista® Business
- Instant converged communications using built-in 1.3 Mega Pixel camera and dual built-in stereo microphones
- Superior security features for enhanced data and hardware protection
- Hot-swappable modular bay device options for ultimate flexibility
- Health and environment friendliness with RoHS compliance¹⁰

* with weight saver option only



	Specifications
Platform	Intel® Centrino® 2 Processor Technology
	- Intel® Core™2 Duo Processor T9400 (2.53GHz, 6MB L2 cache, 1066MHz)/Intel® Core™2 Duo Processor P8600 (2.4GHz, 3MB L2 cache, 1066MHz)
	- Intel® GM45 Express Chipset
	- Intel® WiFi Link 5300AGN (3x3) network connection
Operating System	Genuine Windows Vista® Business
3 - 7 - 1	(or Genuine Windows Vista® Home Premium)
	(or Genuine Windows Vista® Home Basic)
Display	14.1-inch Anti Glare WXGA TFT ¹⁸ 185nits, 1280 x 800 pixels
Modular Bay Device	Dual Layer DVD Super Multi Writer?/ CD-RW Combo Drive
Memory	2GB DDR3 1066MHz/ 1GB DDR3 1066MHz
•	Max. Memory Supported ¹⁴ - 4GB DDR3 1066MHz, Dual-Channel
Hard Disk	320GB/ 250GB/ 160GB
Battery	Up to 3.6hrs¹ (6-cell Li-lon 5800mAh)
Weight	Approx. 2.2kg (w/ weight saver option)
	Detailed Specifications
Hard Disk Drive	SATA-150 5400rpm, S.M.A.R.T support, Two Partitions - 50/50 ¹³ , protected by Fujitsu 3D Shock Sensor ¹⁵
Graphics	Integrated Intel® Graphics Media Accelerator 4500MHD with Intel® Clear Video Technology ¹¹ and DVMT ⁶ 5.0 delivers low-power, high-performance 2D/3D
	graphics with Shader Model 4.0, video and display capabilities at a max. shared memory of 825MB/313MB
High Definition (HD) Audio	RealTek ALC269 HD audio codec with dual built-in stereo speakers
	HD Audio-in: External Mic-in, Dual Built-in Stereo Microphones
	HD Audio-out: Headphone-out
Communication	1.3 Mega Pixel camera, Bluetooth® v2.0+EDR, 56K V.922 Global Modern MDC1.5, 1000/100/10Mbps4 Gigabit Ethernet PCI Express x 1 and Intel® WiFi Link
	5300AGN (3x3) network connection with three antenna. Separate ON/OFF switch for wireless network connection.
User Interface	Spill-resistant Keyboard ¹² : 84-key, 19mm key pitch, 2.7mm key stroke, Quickpoint option
	Intelligent Touch Pad with configurable vertical and horizontal scroll functions
	Fingerprint Sensor with vertical scroll functions
Card Slots	ExpressCard TM /34 /54, Smartcard ⁷ , Secured Digital/ SDHC/ Memory Stick®/ Memory Stick® PRO
Connector Interface	USB 2.0 x 3, VGA (external display), RJ45 (LAN), RJ11 (modem), HDA-in, HDA-out, Power Adapter DC-in, Port Replicator Interface
Quick Launch Panel	Four Programmable Application Launch Buttons (Internet, Email, and two other softwares)
Security ⁸	BIOS Lock, 2-password Hard Disk Lock, LifeBook Lock, Anti-theft Lock Slot, Smartcard7 slot, Fingerprint Sensor, Trusted Platform Module option
Dimensions	334mm (W) x 242mm (D) x 31/35mm (H)
	Bundled Accessories
AC Adapter	Input AC 100~240V, Output DC 19V 80W
Bundled Software	Softex Omnipass, CyberLink PowerDVD™, CyberLink PowerDirector™, Roxio Easy Media Creator, Adobe Acrobat Reader, Fujitsu UpdateNavi¹6,
	Fujitsu 3D Shock Sensor Utility, Fujitsu Power Saving Utility, Fujitsu Hardware Diagnostic Tool, Fujitsu Display Manager, Sun Microsystems Java Runtime,
	Camera Capture Application, Microsoft Office Professional 2007 60-day Convertible Trial ¹⁷
Software on CD	1 year Full Licensed Norman Virus Control with Sandbox Technology and Norman Personal Firewall, Acronis True Image
	Optional Accessories
Port Replicator	Connector Interface:
	USB 2.0 x 4, Headphone-out, Microphone-in, DVI-D, VGA (external display), RJ45 (LAN), PS/2 (keyboard/mouse), Serial, Parallel, Power Adapter DC-in
Modular Bay Options	Replaceable with
	- Bay Battery, 6-cell Li-lon 3800mAh, up to 6.7hrs¹ battery life (Standard + Bay Batteries)
	- Dual Layer DVD Super Multi Writer ^e
	- 2nd SATA HDD Fitting Kit ³
	- DVD/CD-RW Combo Drive
	- Weight Saver
Floppy Disk Drive	External USB 1.44MB FDD
Mouse	Optical USB Black Mouse (Retractable)

- isclamers:
 Results obtained from BAPCo® MobileMark® 2007/Productivity Workbad) performed on systems with maximum battery life settings under laboratory testing environment. Actual battery life will vary based on screen brightness, sound volume settings, running application connected peripherals, power management settings, battery conditioning, and other customer preferences in the real life situation. Built-in bay device or hard drive usage may also have a significant impact on battery life. Note: Battery life is based on Intel® Core™2 Duo Processor Re80.

 Maximum 56Kbps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

- Maximum 56/kps performance varies according to your local service providers' services as well as line condition. V.92 performance is dependent on local service providers' services.

 Only the HDD Housing Kif and screws are provided. HDD on the purchased separately.

 This term does not represent actual data rate of 1000/100/10Mps and simply indicates compliance with IEEE 802.3 In EEE 802.3 and IEEE 802.3 bit standards. Actual maximum data rate depends on network configurations, cable conditions as well as connected devices. Max shared memory depends on system memory capacity, and system configuration. 825/88 refers to 2/68 system memory capacity.

 Name of the operation of the provider has application for smartinarially visponosis to application and system performance. The memory is available to the Operating System will be less than the size of installed memory module.

 Fullss often on provide the application for Smartinarial solution.

 BIOS Lock needs a supervisor/user password to access IRIOS setting. BIOS settings can be configured to prompt for password at every first bootup or all bootup or all bootup or sequences. Access to BIOS setting is needed to configure Hard Disk Lock Hard Disk Lock requires a supervisor/user password to not bard adds. This is a Table Confidentially security feature. LifeBook Lock Requires a supervisor/user password to bootup or all bootup or all bootup or sequences. Access to BIOS setting is sequenced to refer to retire date on the hard disk. This is a Data Confidentially security feature in the Book of the Provision of the Provisio

"PCI Express" and the PCI Express design marks are registered trademarks and/or service marks of PCI-SIG. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

Specifications reflected above are engineering and hardware specifications. They do not represent actual usage or operating dimensions, sizes, performances and weights as these are dependent on factors such as operating temperature, type of operating system and application used, connected devices and accessories as well as hardware configurations of the notebook. Please check the compatibility of 3rd party accessories before purchase. Ambient temperature: 5" to 35°C/ 41 to 95°F (operating), -15" to 60°C/ 5 to 140°F (non-operating), Pelative humothry, 20% to 65% FM (operating), 8% to 85% FM (operating), 8% to











Asia Pacific Ltd Tel: (852) 3101 8133 Fax: (852) 3101 0633 hk.fujitsu.com/pc

HONG KONG (Head Office):

Fuiitsu PC

AUSTRALIA &

NEW ZEALAND: Fujitsu PC Australia Toll Free: (AU) 1800 288 283 (NZ) 0800 288 283

Fax: (61-2) 9889 3360 au.fujitsu.com/pc

Fujitsu PC China Division

Tel: (86-21) 3310 9888 Fax: (86-21) 3310 0606 cn.fujitsu.com/pc

Fujitsu India Limited

Tel: (91) 124 470 5100 Fax: (91) 124 470 5199 in.fujitsu.com/pc

INDONESIA: Fujitsu Indonesia

Tel: (62-21) 570 9330 Fax: (62-21) 573 5150

MALAYSIA:

Fujitsu PC Asia

Pacific Pte Ltd Tel: (60-3) 7728 4868 Fax: (60-3) 7728 4830 my.fujitsu.com/pc

PHILIPPINES: Fujitsu Philippines Inc.

Tel: (63-2) 812 4001 Fax: (63-2) 817 7576 ph.fujitsu.com/pc

SINGAPORE: Fujitsu PC Asia Pacific Pte Ltd

Tel: (65) 6776 0688 Fax: (65) 6776 0788 sg.fujitsu.com/pc

Fujitsu Taiwan Ltd Tel: (886-2) 2311 2255 Fax: (886-2) 2311 2277 tw.fujitsu.com/pc

TAIWAN:

THAILAND: Fujitsu Systems Business (Thailand) Ltd

PC Division Tel: (66-2) 263 7888 Fax: (66-2) 263 7880 th.fujitsu.com/pc

VIETNAM: Fujitsu Vietnam Ltd

Tel: (84-4) 831 3895 Fax: (84-4) 831 3898 vn.fujitsu.com/pc

Note: For countries not listed above, please contact our Hong Kong office.









All rights to the mentioned trademarks reside with their respective owners. Fujitsu endeavours to ensure that the information in the documentation is correct and fairly stated, but does not accept liability for any errors omissions. The development of Fujitsu products and services is continuous and published information may not be up to date. It is important to check the current position with Fujitsu. The document is not part of the contract or licence save in so far as may be expressly agreed.