

SCX-6555N/6545N **MultiXpress** Monochrome Multifunction Printers

Centralized Workflow Solution



The Professional Solution Center

Powerful applications provide businesses with customizable solutions. Samsung's MultiXpress provides high-speed printing and copying with customizable control to increase productivity and maintain economical running cost.

Samsung offers in-house and select partner solutions.

Samsung offers MPS, mobile, security and productivity solutions. These solutions allow you to create a more efficient and secure workgroup.

	Document Management/Workflow		
	 DPD - GoldFax^A Drivve^A Intellinetics^A 	 Perceptive^A Prism^A SmarThru3 (Workflow)* 	
	Managed Print Services		
	 Compass GreatAmerica Leasing 	 LMI MWAi^a PrintFleet 	
	Job Accounting/Pull Printing		
	 Bits^A EFI Equitrac^A Genius Bytes^A ITC Jetmobile 	 OCM^A PaperCut^A Pharos^A SafeCom^A Vendapin 	
	Device Management		
	• SyncThru* (Web Admin)	• SyncThru 6* (Web Services)	
^A XOA platform solution.	* Samsung in-house solution.		



Free Samsung Mobile Print App

Lets you print, scan and fax to/from mobile devices. Just connect to your MFP wirelessly and print, scan or fax without the need to install any drivers.* *Note: Wireless Access Point (AP) is required



The Samsung Mobile Print App earned the 2012 Pick Award from Buyers Lab, Inc.

Protect both resources and data.

Data security is a major concern of businesses today. The Samsung Security Framework is standard on the MultiXpress 6555N and MultiXpress 6545N MFPs. It increases network protection and helps prevent unauthorized access to confidential information.

	Authenticated User	AuthenticationAuthorizationAccounting	
	Protected Network	 Secure Socket Layer (SSL)/ Transport Layer Security (TLS) Simple Network Management Protocol (SNMP) v3 Internet Protocol Security IPSec (Internet Protocol [IP] v4, IPv6) 802.1x with Extensible Authentication Protocol [EAP] Protocol/port management MAC/IP filtering 	
	Secure Document	 Secure print Secure scan Secure fax Document tagging (watermark, stamps) 	
CIN STATE	Secure Data	 Encryption Hard disk drive image overwrite Digital signature 	
	Secure Management	System logsSystem back upEmail notification	
Shown with			

optional equipment.

XOA Express Application Platform*



XOA Express application platform is Samsung's open architecture system that allows you to add custom applications and services on your MFP, so that it can be easily integrated and optimized with your workflow. XOa *XOA model special order only

Scan to Anywhere

The MultiXpress 6555N/6545N helps to distribute documents efficiently by scanning directly to email, FTP, SMB or client.



Document Box

Store scanned data into HDD and manage the stored data. Print and send your scanned data stored on the standard 80GB hard disk drive at any time.



Configurations: Main Unit (520 sheets + MP 100 sheets) + Finishing Options

Accessories



Specifications	MultiXpress 6555N	MultiXpress 6545N	
Print			
Speed*	Up to 55 ppm	Up to 45 ppm	
Resolution	1,200 x 1,200 dpi effective output	1,200 x 1,200 dpi effective output	
First Print Out Time	Less than 8 seconds (from ready mode)	Less than 8 seconds (from ready mode)	
Emulation	PCL5, PCL6, Postscript Level 3, TIFF, JPG, PDF v1.4	PCL5, PCL6, Postscript Level 3, TIFF, JPG, PDF v1.4	
Сору	·		
Speed**	Up to 55 ppm	Up to 45 ppm	
Resolution	600 x 600 dpi	600 x 600 dpi	
First Copy Out Time	Less than 5 seconds	Less than 5 seconds	
Zoom Rate	25-400% (platen), 25-200% (ADF)	25-400% (platen), 25-200% (ADF)	
Copy Features	ID copy, Clone Copy, N-up Copy, Poster Copy, Booklet	ID copy, Clone Copy, N-up Copy, Poster Copy, Booklet	
Scan			
Compatibility	Twain Standard, WIA Standard	Twain Standard, WIA Standard	
Method	Color Flatbed Scanner or DADF	Color Flatbed Scanner or DADF	
Resolution (Optical) / (Enhanced)	600 x 600 dpi / 4,800 x 4,800 dpi	600 x 600 dpi / 4,800 x 4,800 dpi	
Scan to	HDD, USB, Email, Client, SMB, FTP	HDD, USB, Email, Client, SMB, FTP	
Fax			
Compatibility / Modem Speed	ITU-T G3 / 33.6Kbps	ITU-T G3 / 33.6Kbps	
Resolution	Mono: 300 x 300 dpi / Color: 200 x 200 dpi	Mono: 300 x 300 dpi / Color: 200 x 200 dpi	
Memory	HDD Storage (80GB HDD)	HDD Storage (80GB HDD)	
Auto Dialing	Speed Dial: 200 Locations	Speed Dial: 200 Locations	
Fax Features	On-hook Dial, Auto Redial, Last Number Redial, Mail Box, Auto Reduction, Multi Send, Delayed Send, Fax Forwarding (HDD, Email, Fax)	On-hook Dial, Auto Redial, Last Number Redial, Mail Box, Auto Reduction, Multi Send, Delayed Send, Fax Forwarding (HDD, Email, Fax)	
Paper Handling	Tornal ung (hbb, Einall, Fax)	Towarding (hbb, chail, rax)	
Input Capacity and Types	520-Sheet Cassette, 100-Sheet Multi-Purpose Tray	520-Sheet Cassette, 100-Sheet Multi-Purpose Tray	
Output Capacity and Types	Up to 500 sheets Face Down	Up to 500 sheets Face Down	
Media Size	3.86" x 5.83" - 8.5" x 8.5" x 14"	3.86" x 5.83" - 8.5" x 8.5" x 14"	
Media Type	Plain, Thin, Envelope, Labels, Card Stock, Bond, Archived, Punched, Pre-Printed, Recycled, Transparency,	Plain, Thin, Envelope, Labels, Card Stock, Bond, Archived, Punched, Pre-Printed, Recycled, Transparency,	
ADF Capacity	Letterhead, Thick, Colored 100-Sheet DADF	Letterhead, Thick, Colored 100-Sheet DADF	
ADF Document Size	Width: 5.7"-8.5", Length: 5.7" - 14.0" for Single Page Scan, 5.7" - 15.7" for Multi Page Scan	Width: 5.7"-8.5", Length: 5.7" - 14.0" for Single Page Scan, 5.7" - 15.7" for Multi Page Scan	
General Features			
LCD	800 x 480 7" WGA Color Touch Screen LCD	800 x 480 7" WGA Color Touch Screen LCD	
Memory / Storage	256MB (Max 512MB) / 80GB HDD	256MB (Max 512MB) / 80GB HDD	
Processor	500 MHz	500 MHz	
Connectivity	Hi-Speed USB 2.0, Ethernet 10/100/1000 base TX, USB host 2.0 (Scan to and print from USB device)	Hi-Speed USB 2.0, Ethernet 10/100/1000 base TX, USB host 2.0 (Scan to and print from USB device)	
OS Compatibility	(Windows) XP 32/64 bit, Vista 32/64 bit, Windows 7/8 32/64 bit, Windows 2003 Server 32/64 bit, Windows Server 32/64 bit, Vista 32/64 bit) / Linux] RedHat Enterprise Linux WS 4, 5 (32/64 bit) Fedora 5, 6, 7, 8, 9, 10, 11, 12, 13 (32/64 bit) / SuSE Linux 10.1 (32 bit) / OpenSuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / Ubuntu 6.06, 6, 10, 7, 04, 7, 10, 8, 04, 8, 10, 9, 04, 9, 10, 10, 04 (32/64 bit) / SuSE Linux Enterprise Desktop 10, 11 (32/64 bit) / Debian 4, 0, 50 (32/64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / SuSE Linux Server 32/64 bit, Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / SuSE Linux Server 32/64 bit) / SuSE Linux 10.1 (32 bit) / Debian 4, 0, 50 (32/64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / SuSE Linux Server 32/64 bit) / SuSE Linux 5.1 (2, 5, 5, 5, 4/ (Mac) Mac) Mac 20 (2)/64 bit) / SuSE Linux 10.1 (32 bit) / Debian 4, 0, 50 (32/64 bit) / Mandriva 2007, 2008, 2009, 2009.1, 2010 (32/64 bit) / SuSE Linux 5.1 (2, 5, 5, 5, 5, 4/ (Mac) Mac 20 (2)/64 bit) / Debian 4, 0, 50 (32/64 bit) / SuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.0, 11.1, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.0, 11.2, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.0, 11.2, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.0, 11.2, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.2, 11.2 (32/64 bit) / SuSE 10.2, 10.3, 11.2 (32/64 bit) / SuSE 1		
Noise Level	Less than 55 dBA (Printing) / Less than 57 dBA (Copying) / Less than 37 dBA (Standby)	Less than 55 dBA (Printing) / Less than 57 dBA (Copying) / Less than 37 dBA (Standby)	
Duty Cycle, Monthly	Up to 250,000 pages	Up to 200,000 pages	
Dimension (W x D x H)	25.2" x 19.4" x 23.9"	25.2" x 19.4" x 23.9"	
Weight	106.3 lbs.	106.3 lbs.	
Consumables			
Average Toner Cartridge Yield	25,000 standard pages (declared yield in accordance with ISO/IEC 19752)	25,000 standard pages (declared yield in accordance with ISO/IEC 19752)	
Average Drum Yield	80,000 standard pages	80,000 standard pages	
Model Codes	25,000 Page Toner Cartridge (SCX-D6555A) / 80,000 Page Drum (SCX-R6555A)	25,000 Page Toner Cartridge (SCX-D6555A) / 80,000 Page Drum (SCX-R6555A)	
Accessories			
	256MB Memory Module (ML-MEM160) 520 Sheet Cassette Feeder (SCX-56555A) 2,100 Sheet High Capacity Feeder (SCX-HCF100) Fax Kit (SCX-FAX210) 1-Bin Finisher (SCX-FIN115) 2-Bin Finisher (SCX-FIN115) 4-Bin Malibox (SCX-MET40S) Staple Cartridge (SCX-STP000) Short Stand (SCX-DSK105) Tall Stand with Storage Cabinet (SCX-DSK10T) FDI Kit (SCX-KIT20F) 125,000 Yield Service Maintenance (SCX-V6555B) 250,000 Yield Service Maintenance (SCX-V6555A)	256MB Memory Module (ML-ME/III160) 520 Sheet Cassette Feeder (SCX-56555A) 2,100 Sheet High Capacity Feeder (SCX-HCF100) Fax Kit (SCX-FAX210) 1-Bin Finisher (SCX-FIN15) 2-Bin Finisher (SCX-FIN15) 4-Bin Mailbox (SCX-MET40S) Staple Cartridge (SCX-STP000) Short Stand (SCX-DSK105) Tall Stand with Storage Cabinet (SCX-DSK10T) FDI Kit (SCX-KIT20F) 125,000 Yield Service Maintenance (SCX-V6555B) 250,000 Yield Service Maintenance (SCX-V6555A)	
Green Management			
	ENERGY STAR® Compliant, S.T.A.R. (Samsung Takeback and Recycle) Program	ENERGY STAR® Compliant, S.T.A.R. (Samsung Takeback and Recycle) Program	

*Print speed will be affected by operating system used, computing performance, application software, connecting method, media type, media size and job complexity. **Copy speed is based on Single Document Multiple Copy.

Product Support: 1-866-SAM4BIZ | 1-800-SAMSUNG | samsung.com/printer

Follow us: 💟 @SamsungBizUSA | You Tube youtube.com/samsungbizusa

ENERGY STAR AWARD 2012 PARTNER OF THE YEAR Samsung Electronics has been named 2012 ENERGY STAR Partner of the Year in the product manufacturing category by the U.S. Environmental Protection Agency (EPA).



sťarprogram SAMSUNG Toner Recycling Program samsung.com/starus

©2014 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Simulated screen images. Printed in USA on 50% recycled (30% post-consumer waste) paper using soy inks. PNT-6555N6545NBRO-APR14T

