

DATASHEET

FUJITSU ESPRIMO P2550 DESKTOP PC

YOUR IMMEDIATELY AVAILABLE OFFICE PC

ESPRIMO P2550

The ESPRIMO P2550 is designed for price-conscious customers and is equipped with state-of-the-art standard Intel® technology. These systems meet every office requirement - especially those typical for small and medium-sized businesses. The ESPRIMO P2550 is available from your dealer at all times and is thus an ideal choice once the decision to purchase has been taken.

ATTRACTIVE PRICE

PC for the day-to-day challenges of office life

■ Proven Intel® technology

DESIGNED AND ENGINEERED IN GERMANY

Outstanding quality and stable functions based on German production standards

■ The development, production and function tests are all under one roof in Germany

IMMEDIATE AVAILABILITY

Short waiting times once purchase decision has been taken.

■ Preferred versions available on-site







COMPONENTS

PROCESSOR	Intel® Core™2 Quad processor Q8300 (4C/4T, 2.5 GHz, 4 MB, 1333 MHz)
	Intel® Core™2 Duo processor E8400 (2C/2T, 3.0 GHz, 6 MB, 1333 MHz)
	Intel® Core™2 Duo processor E7600 (2C/2T, 3.06 GHz, 3 MB, 1066 MHz)
	Intel® Core™2 Duo processor E7500 (2C/2T, 2.93 GHz, 3 MB, 1066 MHz)
	Intel® Core™2 Duo processor E7400 (2C/2T, 2.8 GHz, 3 MB, 1066 MHz)
	Intel® Pentium® processor E6300 (2C/2T, 2.8 GHz, 2 MB, 1066 MHz)
	Intel® Pentium® processor E5400 (2C/2T, 2.7 GHz, 2 MB, 800 MHz)
	Intel® Pentium® processor E5300 (2C/2T, 2.6 GHz, 2 MB, 800 MHz)
	Intel® Celeron® processor E3200 (2C/2T, 2.4 GHz, 1 MB, 800 MHz)
	Intel® Celeron® processor 450 (1C/1T, 2.2 GHz, 512 KB, 800 MHz)
MEMORY MODULES	1 GB (1 module(s) 1 GB) DDR2, 800 MHz, PC2-6400
	2 GB (1 module(s) 2 GB) DDR2, 800 MHz, PC2-6400
HADD DICK DDIVEC (INTERNAL)	
HARD DISK DRIVES (INTERNAL)	SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.
	SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.
The state of the s	ATI Radeon® HD 3450, 256 MB
	NVIDIA® GeForce® 9300GE, 256 MB
	NVIDIA® GeForce® 9300GE, 512 MB
MODULAR BAY OPTIONS	DVD-ROM, SATA I
	DVD Super Multi, SATA I
	MultiCard Reader 20in1, 3,5-Inch, USB 2.0
INTERFACE ADD ON CARDS/COMPO- NENTS (OPTIONAL)	
	WLAN III, 802.11g/Draft-n (Windows only)
	Modem adapter kit (EU)
	Modem 56k incl. RJ11 modem cable
Base unit	ESPRIMO P2550
MAINBOARD	
Mainboard type	D2950
Formfactor	reduced µATX
Chipset	NVIDIA® MCP73PV
<u> </u>	
Processor socket	LGA 775
Processor socket Processor quantity maximum	LGA 775
Processor socket Processor quantity maximum System bus (FSB / HT / QPI)	LGA 775 1 1333 MHz
Processor socket Processor quantity maximum System bus (FSB / HT / QPI)	LGA 775
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.)	LGA 775 1 1333 MHz
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency	LGA 775 1 1333 MHz 2 DIMM (DDR2)
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s Phoenix 6.0
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version BIOS features	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version BIOS features	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s Phoenix 6.0 BIOS based on Phoenix SecureCore
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version BIOS features Audio codec	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s Phoenix 6.0 BIOS based on Phoenix SecureCore Recovery BIOS
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version BIOS features Audio codec Audio features	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s Phoenix 6.0 BIOS based on Phoenix SecureCore Recovery BIOS Realtek ALC663
Processor socket Processor quantity maximum System bus (FSB / HT / QPI) Memory slots Supported capacity RAM (max.) Memory frequency LAN BIOS version BIOS features Audio codec	LGA 775 1 1333 MHz 2 DIMM (DDR2) 4 GB 800 MHz 10/100/1000 MBit/s Phoenix 6.0 BIOS based on Phoenix SecureCore Recovery BIOS Realtek ALC663

INTERFACES	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
USB 2.0 total	8
USB front	
	2
USB rear	4
USB internal	2
VGA	1
Serial (RS-232)	1 (9pi, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	1/1
Ethernet (RJ-45)	1
INPUT DEVICE / COMPONENTS	
	Optical USB wheel mouse Keyboard
DRIVE BAYS	
Drive bays total	5
3.5-inch internal bays	2
3.5-inch external bays	1
5.25-inch external bays	2
SLOTS	
PCI-Express x16	1 x (240 mm)
PCI-Express x1	1 full height
PCI (32-bit / 33 MHz)	2 x (240 mm) full height
GRAPHICS ON BOARD	
Graphics brand name	NVIDIA® GeForce® 7050
Shared video memory	up to 256 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1024 x 768 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1680 x 1050 pixel 1920 x 1200 pixel
Graphics features	DirectX 9
Graphics notes	Shared memory depending on driver Resolution (color depth up to 32 Bit/pixel) Refresh rates reflect the max. graphics capabilities. Video quality can be deteriorated when using maximum settings. For TFT we recommend using 60Hz
ELECTRICAL VALUES	
Power supply input	200 - 240 V ~1,5A
Power supply input	200 - 240 V ~1,5A
Rated voltage range	200 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	200 - 240 V
Operating line frequency range	47 - 63 Hz
Max. output of power supply	300 W
Monitor outlet	No No
POWER CONSUMPTION	
Power consumption note	See white paper Energy Consumption
	Paka: =

HEAT DISSIPATION	
Heat dissipation notes	See white paper Energy Consumption
NOISE FOR STANDARD CONFIGURATION	N (HDD, ODD, FDD)
Related Processors for noise	Intel® Core™2 Quad Q8300
Noise Operation mode 1: ODD load (Blue angel requirement)	5.1 B / 36 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	4.5 B / 30 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	1 5.1 B / 36 dB(A)
Noise Operation mode 4: High load	5.2 B / 37 dB(A)
Noise Operation mode 5: Office applications	4,7 B / 32 dB(A)
Idle mode (Blue Angel requirement)	4.4 B / 29 dB(A)
DIMENSIONS / WEIGHT / ENVIRONMEN	ΤΔΙ
Dimensions (W x D x H)	175 x 425 x 353 mm
Operating position	Vertical
Weight	approx. 11 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C
COMPLIANCE	FORDIMO POFFO
Product	ESPRIMO P2550
Model	MI4W-D2950
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
OPERATING SYSTEM	
Operating system optional preinstalled	Microsoft® Windows® 7 Professional TwinLoad Microsoft® Windows® XP Professional (DVD)
Operating system compatible	Linux
Operating system notes	All Windows® 7 versions are Office 2007 ready.
ADDITIONAL SOFTWARE	
Additional software (preinstalled)	Nero Essentials S (burning software)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows®
COMPATIBILITY (REFERENCES)	
	DMI 2.0 USB 2.0 WMI 1.5
SECURITY	
Physical security	Kensington Lock support Eye for padlock
System security	Boot sector virus protection Control of external interfaces
User security	User and supervisor BIOS password Optional: Access protection via external SmartCard reader
PACKAGING INFORMATION	
Packaging dimension	500x290x540 mm
Max. quantity / pallet	24
Packaging notes	printed user documentation is bleached in chlorine free process
WARRANTY	
Service level	(depending on country)
Recommended Service	5x9, Response Time: Next Business Day

VARRANTY	
pare Parts availability	3 years
ervice Weblink	http://ts.fujitsu.com/Supportservice

FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO P2550, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructureas-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

MORE INFORMATION

Learn more about Fujitsu ESPRIMO P2550, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. http://ts.fujitsu.com/esprimo

FUJITSU GREEN POLICY INNOVATIOHN

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



COPYRIGHTS

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2010-02-01 CE-EN