Data Sheet
Fujitsu Display B24-8 TS Pro

Advanced display: 60.5 cm (23.8-inch) widescreen
Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B24-8 TS Pro is made for intensive office work. With visual and mechanical ergonomics this stylish black display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

The display provides an excellent visual performance with In-Plane Switching (IPS) technology.

The display enables a convenient and fatigue-proof longtime-usage with oustanding visual ergonomics for the office.

The optimized and relaxed position with ergonomic stand features height adjust, swivel, tilt and 90° rotation.

The display allows for flexible connectivity with DisplayPort, DVI, Analog and USB.

The smart black design with space saving front frame and smart details like discretely integrated speakers and cable guide allows for a clean desk.

The environment-friendly LED technology allows for unique, highly efficient energy saving solutions like ECO operation mode and ECO standby.

Technical details

Special features	
	In-Plane Switching (IPS) technology Eco button for Eco mode and 3-coloured Eco status LED 5-in-1 Stand Cable guide Pivot Always available USB (in operating and standby mode) DisplayView™ Software 24/7 usage Headset connector Integrated speakers
Ergonomic stand	
Stand	5-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	40 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	345°
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors
Brightness - typical	250 cd/m2
Size and resolution	
Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,366 x 768 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Connectivity	
HDMI	1 x HDMI
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio sound output	2 x 2 W
Audio signal input	3.5 mm stereo phone jack
USB downstream	2 x USB 2.0
USB upstream	1 x USB
Ease-of-use menu	
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Mode	sRGB, Office, Photo, Video, Low Blue Light
Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)

Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Resolution/mode, Signal input
Setup	Input select, Language, DDC/CI, OSD-Timeout, Factory preset
Power consumption (typical, w/o sound)	
Soft switch off	0.14 W
Power save mode	0.17 W
Operating with EPA settings	13.9 W
Total Energy Consumption (ETEC)	43.6 kWh/year
Operating maximum brightness	22 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 8.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Model	B24-8 T
Global	EPEAT® Bronze (dedicated regions), TÜV Low Blue Light Certified, TÜV Flicker Free Certified, Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TCO Certified
Europe	EN 62368-1, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Australia/New Zealand	RCM
China	CCC
Germany	TÜV GS
India	BIS
Russia	EAC
Singapore	S-Mark
South Korea	KC
Taiwan	BSMI
USA/Canada	FCC Class B, cTUVus
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	553 x 63.5 x 330.2 mm
	21.77 x 2.5 x 13.00 inch
Dimension with stand (W x D x H)	553 x 229.4 x 347 mm
	21.77 x 9.03 x 13.65 inch
Weight (unpacked)	5.6 kg
	12.35 lbs
Weight (Monitor only)	3.5 kg
	7.74 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Additional software (optional)	WINDOWS WHQL driver DisplayView Suite

Package content	
Display delivered accessories	DVI-D Data cable 1.8 m Audio cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download
Packaging dimension (mm)	
Weight (packed)	7.4 kg
Weight (packed) (lbs)	16.20 lbs

Warranty	
Warranty period	3 years (depending on country)
Spare Parts availability	at least 7 years after shipment, for details see https://support.ts.fujitsu.com/

More information

In addition to Fujitsu Display B24-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures
With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products
www.fujitsu.com/global/products/computing/

Software
www.fujitsu.com/software/

More information

Learn more about Fujitsu Display B24-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
http://ts.fujitsu.com

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax : xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: www.fujitsu.com/[country]
2024-03-06 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions