

Data Sheet

Fujitsu ESPRIMO Q520

The Mini with More PC per cm³

The FUJITSU ESPRIMO Q520, featuring full desktop PC functionality in a stylish and compact housing, is a real eye-catcher on your desk. Latest generation Intel® Core™ processors deliver the performance to meet your daily office needs. The Zero Noise functionality guarantees silent operation. An integrated 90%-efficient power supply cuts your energy bill. The innovative Low Power Active Mode provides businesses with a wide range of new usage scenarios like telephony and video conferencing. Its compact size and wide range of interfaces make the FUJITSU ESPRIMO Q520 your first choice for locations where space saving is key.

An elegant mini PC for challenging office tasks

Eye-catcher on every desk with a modern and exclusive design

- Fully equipped PC with a volume of ~2.0 liters - based on standard desktop technology

Always available office PC

Provides businesses with a wide range of new usage scenarios like telephony and video conferencing

- Combines availability with energy saving. The PC looks like it is off but background application tasks can still run in the Low Power Active Mode

Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and function tests - all under one roof in Germany

Superb usability

Pleasant working environment due to a tidy desk

- Horizontal or vertical operations and an integrated VESA mount, service door for easy upgrade of major components

Latest technology

Get your office job done fast and reliable

- 4th generation Intel® Core™ processor family



Components

Processor	Intel® Core™ i7-4785T processor (4 Cores / 8 Threads, 2.20 GHz, up to 3.2 GHz, 8 MB, Intel® HD Graphics 4600) * Intel® Core™ i5-4590T processor (4 Cores / 4 Threads, 2.00 GHz, up to 3.0 GHz, 6 MB, Intel® HD Graphics 4600) * Intel® Core™ i3-4170T processor (2 Cores / 4 Threads, 3.20 GHz, 3 MB, Intel® HD Graphics 4400) *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)
Operating systems	
Operating system pre-installed	Windows 8.1 Pro Windows 8.1 Windows 7 Professional 64-bit Windows 7 Professional 32-bit
Operating system compatible	Windows 10 Pro (license + recovery media only) openSUSE Linux
Memory modules	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1,600 MHz, PC3-12800, SO DIMM 4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1,600 MHz, PC3-12800, SO DIMM 8 GB (1 module(s) 8 GB) DDR3, non-ECC, 1,600 MHz, PC3-12800, SO DIMM
Hard disk drives (internal)	HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch* SSD SATA III Premium, 512 GB, 2.5-inch SSD SATA III Premium, 256 GB, 2.5-inch SSD SATA III Premium, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch SSD SATA III, 256 GB, 2.5-inch, SED SSD SATA III, 128 GB, 2.5-inch, SED SSHD SATA III, 5,400 rpm, 500 GB, 2.5-inch HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch* HDD SATA II, 5,400 rpm, 320 GB, 2.5-inch*
Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery SSHD (Solid State Hard Disk, Hybrid drive) SSD (Solid State Disk) SED (Self-Encrypting Drive)
Graphics	DP to DVI-D (single link) Adapter Cable
Drives (optional)	DVD Super Multi Slot-in slim
Interface add on cards/components (optional)	WLAN 802.11 a/g/n (2x2) and Bluetooth (dedicated regions only, not for Indonesia)

Base unit

Base unit	ESPRIMO Q520
Mainboard	
Mainboard type	D3223
Formfactor	proprietary
Chipset	Intel® H81
Processor socket	LGA 1150

Mainboard

Processor quantity maximum	1
Supported capacity RAM (max.)	16 GB
Memory slots	2 SO DIMM (DDR3, 1600 MHz)
Memory frequency	1,600 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same
LAN	10/100/1,000 MBit/s Intel® I217LM
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC671
Audio features	Buzzer

I/O controller on board

Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-out / headphone	1
Audio: line-in / microphone	1
USB 2.0 total	4
USB 3.1 Gen1 (USB 3.0) total	2
USB front	2x 3.0
USB rear	4x 2.0
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Ethernet (RJ-45)	1
Multicardreader	1 (SD, MMC)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB wheel mouse
Input devices (optional)	KBPC PX ECO Mouse M440 ECO

Drive bays

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim slot-in for 5.25"

Graphics on board

Graphics brand name	Intel® HD Graphics, HD Graphics 4400, HD Graphics 4600 (depending on processor)
Shared video memory	up to 1,782 MB

Graphics on board

TFT resolution (VGA)	1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel
TFT resolution (DVI)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel 1,920 x 1,200 pixel 2,560 x 1,440 pixel 2,560 x 1,600 pixel 3,840 x 2,160 pixel (requires Intel® Core™ i3, i5 or i7 processor)
Graphics features	Dual display support DirectX® 11.1 HDCP support Open CL® 1.2 OpenGL® 4.0 One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 115V/230V; 10% / 20% / 50% / 100% load) : 83% / 87% / 90% / 88%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	65 W (integrated in system)
Power factor correction/active power	No (meets input harmonic current according EN61000-3-2)

Power consumption

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=5000c21d-e2f0-4511-b9c0-9dd01c57b8a4

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise emission

Related Processors for noise	Intel® Core i7-4765T
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise operation mode: CPU 50% load	tbd
Standard noise operation mode: HDD load	3.0 B / 17 dB(A) Bystander ; 19 dB(A) Operator position

Noise emission

Standard noise operation mode: Idle mode	SSD: no noise emission, 2.5" HDD: 3.0 B / 17 dB(A) Bystander ; 17 dB(A) Operator position
Standard noise operation mode: ODD load	4.5 B / 31 dB(A) Bystander ; 34 dB(A) Operator position
Standard noise operation mode: Office applications 2.0	SSD: no noise emission, 2.5" HDD: 3.0 B / 17 dB(A) Bystander ; 18 dB(A) Operator position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise operation mode: HDD load	3.2 B = 32 dB
Blue angel noise operation mode: Idle mode	3.1 B = 31 dB
Blue angel noise operation mode: ODD load	4.7 B = 47 dB

Dimensions / Weight / Environmental

Dimensions (W x D x H)	185 x 191 x 58.7 mm 7.28 x 7.52 x 2.31 inch
Operating position	Vertical / horizontal (no feet needed)
VESA mount	integrated (100 mm), applicable for selected monitors only, additional mounting kit for specific monitors optional
Weight	1.6 kg
Weight (lbs)	3.53 lbs
Weight notes	Weight may vary depending on actual configuration (without ODD)
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	ESPRIMO Q520
Model	MPC2
Germany	TÜV GS Blauer Engel / Blue Angel
Europe	CE
USA/Canada	FCC Class B cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) EPEAT® Gold (dedicated regions) ENERGY STAR® 6.0 (dedicated regions)
Compliance notes	This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Win7: Fujitsu Recovery (hard disk based recovery) Win8: Microsoft Push Button Recovery (hard disk based recovery) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Manageability link	http://www.fujitsu.com/fts/manageability

Security

Physical Security	Kensington Lock support Housing Lock Plate (to use with Kensington lock)
System and BIOS Security	Boot sector virus protection Write protect option for the Flash EPROM Control of external interfaces External USB ports can be disabled separately Embedded security (TPM 1.2) (optional)
User Security	User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional)

Serviceability**Packaging information**

Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	84
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	If keyboard is included in packaging: 1.) packaging dimension is increasing to: 500 x 208 x 290mm / (19.69 x 8.19 x 11.42 inch); 2.) material weight of carton will increase to 880g; 3.) max. quantity/pallet = 56; printed user documentation is bleached in chlorin free process;

Warranty

Warranty period	1 year (for countries in EMEA)
Warranty type	Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations)

Product Support Services - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life

Recommended Accessories

USB 3.0 Port Replicator PR08



The FUJITSU USB 3.0 Port Replicator PR08 is the perfect solution for hot-desk environments. It connects your notebook to all of your peripherals with a single USB 3.0 plug. The highlight is the internal powerful Display Link chipset that offers an excellent graphic performance. Order Code: S26391-F6007-L400

Display B22W-7 LED



The FUJITSU Display B22W-7 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand. Order Code: S26361-K1472-V140

Display B24W-7 LED



The FUJITSU B24W-7 LED Display with excellent ergonomics makes intensive office work extremely comfortable. This highly reliable display offers superb usability and power-saving features to help reduce your labor as well as energy costs. With wide viewing angle technology, flexible connectivity, and easy manageability, the FUJITSU B24W-7 LED Display can help you improve productivity. Order Code: S26361-K1497-V140

SOUNDSYSTEM DS E2000 Air



The new more powerful SOUNDSYSTEM DS E2000 Air gives you impressive, well-balanced sound throughout the frequency band. It is an unbeatable USB speaker set with a surprisingly small form factor. The robust satellite speakers are decorated with a deluxe piano finish and the base is adorned with warm ambient lighting. Order Code: S26391-F7128-L600

UC&C USB Headset Stereo H650e



The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity. Order Code: S26391-F7139-L10

Wireless Keyboard Set LX901



The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption. S26381-K565-L4** (**: Country specific variation)

More information

In addition to Fujitsu ESPRIMO Q520, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO Q520, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com>

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

Address: x-xx-x, street, city, state, ZIP code, country
Phone: xx-xxxx-xxxx
Fax: xx-xxxx-xxxx
Email: xxx.xxxxx@xx.fujitsu.com
Website: [www.fujitsu.com/\[country\]](http://www.fujitsu.com/[country])
2017-05-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions